



HIGH PERFORMANCE DPC

Radbar High Performance DPC is manufactured from a blend of high-quality virgin polymers, resulting in a high puncture and tear resistance. High Performance DPC is suitable for use on multi-story buildings up to 18m and has high mortar bond properties due to its class leading embossing. Radbar High Performance DPC complies with BS EN 14909:2012, BRE 211 and current UK Building Regulations in relation to Damp-Proof courses and radon protection.

Thickness	600µm
Width	100mm – 1200mm
Length	20m
Colour	Grey
Radon Permeability (10 ⁻¹² m ² /s)	6
Radon Transmittance (10 ⁻⁹ m/s ⁻¹)	5
Water Vapour Transmittance (g/m ² /day)	0.1
Tear Strength (Nail) (N)	>700
Tensile Strength (N/mm ²)	>22
Durability (heat ageing)	Pass
Resistance to Low Temperature	Pass @ -40°C

Accessories available from the Radbar range:

- Jointing tape, double-sided and overlap tape
- Top Hats, for sealing pipe penetrations
- Radon Sumps
- Pre-formed corners
- Detailing Strip, self-adhesive for corners and penetrations
- Protection Boards, for protecting the membrane post installation



sales@capitalvalleyplastics.com



01495 772255